

TECHNICAL DATA SHEET

Packaging	Code
4 x 4 L (1.06 US gal)	2242278001
20 L (5.28 US gal)	2242334001

Description:

EP83 is a high performance, ultra low odour, butyl free, ammonia free floor stripper. It has been specially designed to remove conventional zinc crosslinked finishes as well as environmentally preferable zinc free floor finishes.

EP83 is a highly concentrated rapid response stripper that dissolves multiple coats of finish without the strong and unpleasant odour associated with conventional strippers. EP83 rinses quickly without leaving residual alkali to interfere with finish application. All ingredients in this product are readily biodegradable in accordance with OECD 301 standard.

Av-mixx Use Directions:

****Please note: To avoid excess foaming, place Av-mixx hose at the bottom of the spray bottle and/or bucket.**

- 1) FOR BUCKET OR AUTOSCRUBBER APPLICATIONS: Using the Av-mixx dilution control system, fill either an autoscrubber or mop bucket using the high flow button (select button with the mop bucket icon) and cold water. EP83 Floor Stripper will automatically be diluted at 1:20.
- 2) FOR SPRAY BOTTLE APPLICATIONS: Using the Av-mixx dilution control system fill a properly identified spray bottle using the low flow button (select button with the spray bottle icon) and cold water. EP83 Floor Stripper will automatically be diluted at 1:20.
- 3) Apply liberally to floor surface and keep the floor surface wet with the stripper solution for 5 to 10 minutes depending upon build-up of finish.
- 4) Agitate using a mop, a floor machine or an autoscrubber fitted with an appropriate stripping pad.
- 5) Pick up the stripping solution and residues using a wet vacuum or autoscrubber. Re-apply stripping solution and agitate if needed.
- 6) Thoroughly rinse floor with cold water to remove left over residues from stripping.

Allow floor to dry before applying a floor finish.

Follow all Federal, Provincial and local regulations regarding waste disposal.

Standard Use Directions:

**** Please note: To avoid excess foaming, pour water first and then EP83.**

- 1) Dilute 1 part EP83 with 20 parts cold water and test in small area to verify compatibility with floor before applying generally.
- 2) Apply liberally to floor surface and keep the floor surface wet with the stripper solution for 5 to 10 minutes depending upon build-up of finish.
- 3) Agitate using a mop, a floor machine or an autoscrubber fitted with an appropriate stripping pad.
- 4) Pick up the stripping solution and residues using a wet vacuum or autoscrubber. Re-apply stripping solution and agitate if needed.
- 5) Thoroughly rinse floor with cold water to remove left over residues from stripping.

Allow floor to dry before applying a floor finish.

Security:

HEALTH	3
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	X
X =	See SDS
0 =	Insignificant
1 =	Slight
2 =	Moderate
3 =	High
4 =	Extreme

Note:

The data presented herein is based on experiments and information believed reliable. However, we can make no guarantee on performance of, or results obtained through the use of the product herein described owing to varying conditions in laboratories and plants over which we have no control. Neither can any guarantee be given that the products or uses outlined will not infringe any existing patents.

Technical Specifications:

Appearance	Clear Liquid
Colour	Colorless to slight yellow
Odour	Orange
Specific Gravity	0.975 – 0.995
pH	11.5 – 12.5

